



## BELT PRESS EBP580



**Gross price:**  
**210 590 €**

Net price:  
171 211 €

Belt press with pneumatic belt tensioner, automatic belt control, high pressure belt cleaner and optional brush cleaning system for the belt. The mash is applied to the belt in a uniform layer by the adjustable metering box, at the end of the pressing sequence the pomace is removed from the belt by a scraper. In combination with our WALC and WAR65 washing systems, the level of the metering box is automatically supervised and controlled.

### Processable materials

Apples, Pears, Quince, Carrots, Beetroot, Manioc, Vegetables. This represents just an example, based on different materials and a selection of fruit processed in practice.

### Technical data

|                                |                             |
|--------------------------------|-----------------------------|
| Height pomace ejector          | 745 mm                      |
| Height waste water drain       | 86 mm                       |
| Height juice outlet            | 305 mm                      |
| Connection for juice outlet    | 1 ½ "                       |
| Connection for waste water     | DN75                        |
| Water consumption for cleaning | 3 l/min                     |
| Belt speed                     | 2,1 - 5,5 (stufenlos) m/min |
| Juice yield                    | 75 %                        |
| Material                       | 1.4301 / AISI 304           |



|                       |                                                              |
|-----------------------|--------------------------------------------------------------|
| Weight                | 665 kg                                                       |
| Conveyor width        | 240 - 460 mm                                                 |
| Belt width            | 580 mm                                                       |
| Discharge height      | 1 290 mm                                                     |
| Height                | 1 290 mm                                                     |
| Width                 | 1 270 mm                                                     |
| Length                | 2 145 mm                                                     |
| Electrical protection | 16 A                                                         |
| Connected load        | 400V 50Hz (dreiphasig)                                       |
| Motor rating          | Antriebsmotor 0,75 (1,02) Reinigungsmotor 0,37 (0,5) kW (PS) |
| Nominal rating kg/h   | up to 1 000 kg/h                                             |

## DEVICE SPECIFICATIONS

Weight: **665 kg**

Country of origin: **Austria**

Producer warranty: **2 years**

Electric power supply: **400V 50Hz (3 fazy)**

Nominal rating kg/h: **1000 kg/h**

Juice yield: **75%**

## GALLERY

