CLEANING HEAD ERD

The RD consits of two identical inversely-rotating 55mm heads boasting a 360° spray coverage. Applications: For complete cleaning of production, transportation as well as storage tank interiors.

ARTICLE-NO.	RD
Drives	Water-hydraulic, electric or compressed air
Shaft length	140 / 170 / 300 (water-hydraulic only) 500 / 700 / 1000 / 1500 / 2000 individual specialty lengths = 500 to 4000 [mm]
Working pressure	Up to 200 [bar]
Flow rate	Up to 80 [l/min]
Temperature	-30 to +120 [°C]
Nozzles	Number of 4, angle 0° / 5° / 15°, thread 1/8‘‘
Water connection	3/8‘‘ / 1/2‘‘ / M22x1,5
Opening size for installation	Ø > 78 [mm]
Material	Cleaning head and shaft entirely 316L
Sealant	FPM Viton / FFKM Perfluor / EPDM

Destiller - Anna i Seweryn Fabijaniak
ul. Grunwaldzka 37
37-560 Pruchnik
Tel.: +48 660 143 042
E-mail: biuro@destiller.pl

GALERIE

DESTILLER

Destiller - Anna i Seweryn Fabijaniak
ul. Grunwaldzka 37
37-560 Pruchnik
Tel.: +48 660 143 042
E-mail: biuro@destiller.pl

Godziny pracy
Poniedziałek - piątek 8:00 - 18:00
www.destiller.pl